



DECLARATION OF PERFORMANCE

No. 095

1. Unique identification code of the product-type:

charBIT[®] ELAST PV S42 FINAL

charBIT[®] ELAST PV S42 HQ FINAL

Product type name alternatives: ELAST PV S42 FINAL, ELAST PV S42 HQ FINAL

2. Intended use:

Flexible sheets for waterproofing – Reinforced bitumen sheets for roof waterproofing
(EN 13707:2004+A2:2009)

It is used as final layers for roof deck waterproofing.

3. Manufacturer:

Charvát a.s., Družstevní 289, 517 42 Doudleby nad Orlicí, Czech Republic, tel.: +420 494 383 431

4. Authorised representative:

The manufacturer has no representative on the market.

5. Systems of AVCP:

System 2+

- 6a. Harmonised standard:

EN 13707:2004+A2:2009

Notified body:

Technický a zkušební ústav stavební Praha, s.p.

Oznámený subjekt 1020

Notified Body carried out a supervision including assessing and evaluating the management system in terms of the ability of the system to ensure achievement of the declared product performance according to System 2+ and issued Certificates of Production Management Conformity No. 1020-CPR-050015906.

- 6b. European Assessment Document:

Not applicable.



7. Declared performances:

Essential characteristics	Performance ELAST PV S42 FINAL	Performance ELAST PV S42 HQ FINAL	Harmonised technical specification
External fire performance	B _{ROOF} (t1)	B _{ROOF} (t1)	EN 13707:2004+A2:2009
Reaction to fire	class E	class E	
Watertightness	pass	pass	
Tensile properties:			
Tensile strength in longitudinal direction	900±200 N/50 mm	900±200 N/50 mm	
Tensile strength in transverse direction	700±200 N/50 mm	700±200 N/50 mm	
Elongation in longitudinal direction	45±10 %	45±10 %	
Elongation in transverse direction	45±10 %	45±10 %	
Resistance to roof penetration	NPD	NPD	
Resistance to static loading	10 kg	10 kg	
Resistance to impact	800 mm	800 mm	
Resistance to tearing (nail shank)	250±50 N	250±50 N	
Joint strength	NPD	NPD	
Durability			
Artificial ageing behaviour:			
Flexibility at low temperature (pliability)	-15°C	-25°C	
Flow resistance at elevated temperature	100°C	110°C	
Flexibility at low temperature (pliability)	-15°C	-25°C	
Dangerous substances*	-	-	

*The product contains no hazardous substances.

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

Not applicable.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacture identified above.

Signed for and on behalf of the manufacturer by:

Jindra Kynclová, sales director

At Doudleby nad Orlicí on 2.5.2019



CHARVÁT
akciová společnost
Družstevní 289
517 42 Doudleby nad Orlicí
(PVJ)